

HOT SPOT® COLLECTION



Frog® @ease® In-Line
Cartridge Ready



FiberCor®
High-Density Insulation



Moto-Massage®

SX



*Shown with Alpine White Shell
and Havana Cabinet.*

People	Seating	Jets	Voltage
3 Seats	Open	18 Jets	115 V or 230 V

Size
6' x 6'5" x 33" | 183 cm x 196 cm x 84 cm

Water Care
FROG® In-Line Cartridge Ready

HOT SPOT® COLLECTION

SX



SHELL COLORS*



CABINET COLORS*



COVER COLORS



LEGENDARY MESSAGE

18 Personalized-Control Jets

- 1 Moto-Massage® jet
- 1 XL Rotary Hydromassage jet
- 16 Directional Precision® jets

EASY WATER CARE

Water Care System FROG® In-Line Cartridge Ready
Filtration System 30 sq. ft., top loading

LEADING ENERGY EFFICIENCY

Jet Pump Wavemaster® 6200; Two-speed, 1.5 HP Continuous Duty, 3.2 HP Breakdown Torque
Circulation Pump SilentFlo 5000® for quiet continuous filtration (optional)
Heater No-Fault® 1,000 W / 115 V or 4,000 W / 230 V
Insulation FiberCor® Insulation; Certified to California Energy Commission (CEC) and APSP 14 energy efficiency standards for portable spas
Cover 3.5" to 2.5" tapered, 1.5 lb. density foam core

SIZE

Dimensions 6' x 6'5" x 33" / 183 cm x 196 cm x 84 cm

CAPACITY

Seating Capacity 3 seats
Water Capacity 230 gallons / 870 liters
Weight 645 lbs. / 295 kg dry; 3,090 lbs. / 1,400 kg filled**

ADDITIONAL FEATURES

Smart Spa Technology Hot Spring Spas App, Powered by the Connected Spa Kit
Cover Lifters CoverCradle®, CoverCradle II, or Lift 'N Glide®
Steps Hot Spot Collection Step (Almond, Havana, and Storm), Polymer Step (Ash)
Control System IQ 2020® with LCD control panel
115 V / 20 amp,* 60 Hz (Includes G.F.C.I. protected power cord) or 115 V / 30 amp* or 230 V / 50 amp,* 60 Hz
Lighting System Interior: 6 multi-color LED points of light, dimmable

*Actual colors and products may vary from print representation. See dealer to verify.

**Includes water and 7 adults weighing 175 lbs. each.

*Requires a dedicated circuit supplied to the unit at all times. Electrical requirements will vary outside the U.S.

•G.F.C.I. protected sub-panel required in 30 amp conversion or 220 V mode. Export models available in 230 V, 50 Hz, 1,000 W heater.