HOT SPOT® COLLECTION



Frog® @ease® In-Line Cartridge Ready



FiberCor® High-Density Insulation



Exterior Lighting

PACE



People Seating Jets Voltage

5 Seats Lounge 24 Jets 115 V or 230 V

Size

6′10″ x 6′10″ x 33″ | 208 cm x 208 cm x 84 cm

Water Care

FROG® In-Line Cartridge Ready



HOT SPOT® COLLECTION

PACF





SHELL COLORS*









Alpine

Pearl

Pebble

Tuscan Sun

CABINET COLORS*







Almond

Havana

Storm

COVER COLORS





Nutmeg

LEGENDARY MASSAGE

24 Personalized-Control Jets

- 3 XL Directional Hydromassage jets
- 2 Directional Hydromassage jets
- 2 Rotary Hydromassage jets
- 17 Directional Precision® jets

EASY WATER CARE

Cover

Water Care System FROG® In-Line Cartridge Ready

Filtration System 30 sq. ft., top loading

LEADING ENERGY EFFICIENCY

Jet Pump Wavemaster® 6200; Two-speed, 1.5 HP Continuous Duty,

3.5" to 2.5" tapered, 2 lb. density foam core

3.2 HP Breakdown Torque

No-Fault $^{\odot}$ 1,000 W / 115 V or 4,000 W / 230 V Heater FiberCor® Insulation; Certified to California Insulation Energy Commission (CEC) and APSP 14 energy efficiency standards for portable spas SIZE

Dimensions 6'10" x 6'10" x 33" / 208 cm x 208 cm x 84 cm

CAPACITY

Seating Capacity 5 seats

300 gallons / 1,135 liters **Water Capacity**

Weight 775 lbs. / 350 kg dry; 4,150 lbs. / 1,880 kg filled**

ADDITIONAL FEATURES

Smart Spa Technology Hot Spring Spas App, Powered by the Connected Spa Kit

SmartJet™ System Included

Water Feature Included

Cover Lifters CoverCradle®, CoverCradle II, Lift 'n Glide®, or UpRite® Steps Hot Spot Collection Step (Almond, Havana, and Storm),

Polymer Step (Ash)

Entertainment Wireless Sound System

Control System IQ 2020® with LCD control panel 115 V / 20 amp,*60 Hz (Includes G.F.C.I. protected power cord)

or 115 V / 30 amp* or 230 V / 50 amp,* 60 Hz

Lighting System Interior: 10 multi-color LED points of light

Exterior: 4 multi-color LED points of light

^{*}Actual colors and products may vary from print representation. See dealer to verify.

^{**}Includes water and 7 adults weighing 175 lbs. each

[★]Requires a dedicated circuit supplied to the unit at all times. Electrical requirements will vary outside the U.S.