

FreshWater® Salt System Ready



Dual Action Filtration SilentFlo Circulation



FiberCor® High-Density Insulation



Color LCD Display

### LIMELIGHT<sup>®</sup> COLLECTION

## BEAM




Water Care FreshWater<sup>®</sup> Salt System Ready



# LIMELIGHT° COLLECTION $\mathsf{BEAM}^{\mathsf{T}}$



#### SHELL COLORS\*



#### LEGENDARY MASSAGE

#### **19** Personalized-Control Jets

- 1 XL Dual Rotary jet
- 2 Standard Single Rotary jets
- 2 Standard Directional jets
- 14 Directional Precision® jets

#### EASY WATER CARE

Water Care System	FreshWater <sup>®</sup> Salt System Ready
Filtration System	Dual action, 100 sq. ft., top loading

#### LEADING ENERGY EFFICIENCY

Jet Pump	<b>Beam I</b> Wavemaster® 7000; Two-speed, 1.65 HP Continuous Duty, 3.5 HP Breakdown Torque
	<b>Beam II</b> Wavemaster <sup>®</sup> 9000; Two-speed, 2.5 HP Continuous Duty, 5.2 HP Breakdown Torque
<b>Circulation Pump</b>	SilentFlo 5000® for quiet, continuous filtration
Heater	<b>Beam I</b> Titanium No-Fault® 1,500 W / 115 V or 6000w / 230v
	<b>Beam II</b> Titanium No-Fault® 6,000 W / 230 V
Insulation	FiberCor <sup>®</sup> Insulation; Certified to California Energy Commission (CEC) and APSP 14 energy efficiency standards for portable spas
Cover	3.5" to 2.5" tapered, 2 lb. density foam core

#### SIZE

**Dimensions** 6'8" x 6'8" x 33" / 203 cm x 203 cm x 84 cm

#### CAPACITY

Seating Capacity	4 seats
Water Capacity	295 gallons / 1,115 liters
Weight	700 lbs. / 320 kg dry; 3,860 lbs. / 1,750 kg filled**

#### ADDITIONAL FEATURES

Smart Spa Technology	Hot Spring Spas App, Powered by the Connected Spa Kit
Water Feature	Vidro® backlit ribbon waterfall
Cover Lifters	CoverCradle $^{\otimes},$ CoverCradle II, Lift 'n Glide $^{\otimes},$ or UpRite $^{\otimes}$
Steps	Limelight Collection Step (Coastal Gray, Espresso, and Sable), Polymer Step (Ash)
Entertainment	Bluetooth® Wireless Sound System (Optional)
Control System	Beam I IQ 2020® with LCD control panel 115 V / 20 amp, 60 Hz (Includes G.F.C.I. protected power cord) or 230 V / 50 amp, 60 Hz
	<b>Beam II</b> IQ 2020® with LCD control panel 230 V / 50 amp, 60 Hz (Includes G.F.C.I. protected sub-panel)
Lighting System	Raio® multi-color interior points of light Exterior multi-color lighting with timer
Cooling System	CoolZone™ (Optional)

HotSpring